

NoVoTronic 19

- + Variable possibility of combine connection compartment and profile
- + 2 enclosure sizes 28HP and 42HP
- + Optional with transparent cover
- + Variable length by profile technic

Included in delivery

Enclosure system - depending on version either with connection compartment, swivel intermediate frame, profile and screwed lid.

Technical data

Material:	Enclosure profile: DIN EN 573 EN AW-AlMgSi, Connection component: DIN EN 1706 EN AC-AISI 12 (Fe)
Colour:	Powder coating, RAL 7043, traffic grey B
Ingress protection:	IP 65 to EN 60529, Outdoor application on request
Temperature range:	-40°C to +90°C with transparent cover: -40°C to +60°C

Product range

Product type	Order number	Dimensions H x W x D (mm)
NT 19-03	07.60 28 03	256 x 270 x 139

Accessories

table feet

Order number

10.07 00 19

Socket wrench

Order number

Description of accessories

07.60 00 02

special version for connection room

Front plate

Order number

07.60 28 30

Spare latch

Order number

Description of accessories

07.60 00 04

for connection compartment lid (plastic) for NoVoTronic

Partition wall

Order number

07.60 28 85

Turn bolt fastener

Order number

Description of accessories

07.60 00 01

cylinder lock for transparent cover

Mounting plate

Order number

Description of accessories

07.28 00 30

for connection compartment (28 TE version)

Certificates

No approvals