

# Mini-Polyglas



- + Mini polyglas enclosure with hidden external hinge for MCR technology
- + Standard version or with window

## Included in delivery

Enclosure consisting of base and door;  
please order door lock separately, press-  
in inserts in base for internal mounting

## Technical data

<b>Material:</b>	glass fibre reinforced thermoset polyester
<b>Certificates:</b>	E66473
<b>Colour:</b>	RAL 7038, agate grey, special colour on request
<b>Ingress protection:</b>	IP 66 to EN 60529
<b>Flammability:</b>	self-extinguishing, UL 94 V-0
<b>Insulation:</b>	fully insulated VDE 0100
<b>Disruptive strength:</b>	18 KV/mm, IEC 60243-1
<b>Toxicity:</b>	halogen free
<b>Surface resistance:</b>	$>10^{12}$ Ohm to IEC 60093
<b>opening angle:</b>	120°
<b>Temperature range:</b>	-40°C to +100°C with transparent window: -40°C to +80°C

## Product range

Product type	Order number	Dimensions H x W x D (mm)
MIPT 2	22.16 26 00	160 x 260 x 100

## Accessories

### Socket wrench

Order number	Description of accessories
<b>10.04 70 05</b>	phillips screw
<b>10.04 70 03</b>	triangular 8mm
<b>10.04 70 04</b>	square 8mm

### locking screws

Order number	Description of accessories
<b>21.63 00 03</b>	triangular screw 8mm
<b>21.63 00 04</b>	square screw 8mm (2 pcs)
<b>21.63 00 05</b>	phillips screw (2 pcs)
<b>21.63 00 24</b>	square screw 6mm (2 pcs)

### Mounting plate

Order number
<b>10.01 12 08</b>

### External mounting brackets

Order number	Description of accessories
<b>10.03 10 08</b>	set = 4 pcs

## Certificates

UL 508