



- + Aluminium profile enclosure system in 5 dimensions for data, PC and MCR technology
- + External screw channels guarantee internal area without splinter
- + Integrated guide grooves for PCB's
- + Variable length by profile system

### Included in delivery

Enclosure with 2 Aluminium diecast lids and 2 multi-function profiles, not screwed

## Technical data

<b>Material:</b>	Lid: Aluminium DIN EN 1706 EN AC-AISI 12 (Fe), Enclosure profile: DIN EN 573 EN AW-AMgSi
<b>Colour:</b>	Powder coating, RAL 3003, ruby red for the multi-functional profile, RAL 9005, jet black
<b>Ingress protection:</b>	IP 65 to EN 60529
<b>Temperature range:</b>	-40°C to +90°C with transparent cover: -40°C to +60°C

## Product range

Product type	Order number	Dimensions H x W x D (mm)
NT 160-SL	<b>07.50 30 99</b>	190 x 90 x

## Accessories

### battery insert unit

Order number	Description of accessories
<b>83.90 00 03</b>	for 9V block
<b>83.90 00 06</b>	for 4x AA cells

### Transparent cover

Order number	Description of accessories
<b>07.50 90 10</b>	IP 40

### Wall holder

Order number
<b>07.50 90 05</b>

### Wall profile

Order number	Description of accessories
<b>07.50 91 99</b>	(2 pieces) to insert in system groove for wall fixing

### PCB profile adjustable

Order number	Description of accessories
<b>07.50 92 16</b>	for Novotronic 160

## Certificates

No approvals