

NoVoTronic 19

- + Variable possibility of combine connection compartment and profile
- + 2 enclosure sizes 28HP and 42HP
- + Optional with transparent cover
- + Variable length by profile technic

Included in delivery

Enclosure system - depending on version either with connection compartment, swivel intermediate frame, profile and screwed lid.

Technical data

| | |
|----------------------------|---|
| Material: | Enclosure profile: DIN EN 573 EN AW-AlMgSi, Connection component: DIN EN 1706 EN AC-AISI 12 (Fe) |
| Colour: | Powder coating, RAL 7043, traffic grey B |
| Ingress protection: | IP 65 to EN 60529, Outdoor application on request |
| Temperature range: | -40°C to +90°C with transparent cover: -40°C to +60°C |

Product range

| Product type | Order number | Dimensions H x W x D (mm) |
|--------------|--------------------|---------------------------|
| NT 19-01 | 07.60 28 01 | 256 x 270 x 110 |

Accessories

table feet

Order number

10.07 00 19

Socket wrench

Order number

Description of accessories

07.60 00 02

special version for connection room

Spare latch

Order number

Description of accessories

07.60 00 04

for connection compartment lid (plastic) for NoVoTronic

Partition wall

Order number

07.60 28 85

Mounting plate

Order number

Description of accessories

07.28 00 30

for connection compartment (28 TE version)

Certificates

No approvals