

- + Variable possibility of combine connection compartment and profile
- + 2 enclosure sizes 28HP and 42HP
- + Optional with transparent cover
- + Variable length by profile technic

### Included in delivery

Enclosure system - depending on version either with connection compartment, swivel intermediate frame, profile and screwed lid.

## Technical data

|                            |   |
|----------------------------|---|
| <b>Material:</b>           | Enclosure profile: DIN EN 573 EN AW-AlMgSi,<br>Connection component: DIN EN 1706 EN AC-AISI 12 (Fe) |
| <b>Colour:</b>             | Powder coating, RAL 7043, traffic grey B  |
| <b>Ingress protection:</b> | IP 65 to EN 60529, Outdoor application on request   |
| <b>Temperature range:</b>  | -40°C to +90°C<br>with transparent cover: -40°C to +60°C  |

## Product range

| Product type | Order number       | Dimensions H x W x D (mm) |
|--------------|--------------------|---------------------------|
| NT 19-11 EMC | <b>07.61 28 25</b> |                           |

## Accessories

### table feet

Order number

**10.07 00 19**

### Front plate EMC

Order number

**07.61 28 30**

### 19" mounting frame

Order number

**07.60 28 81**

### mounting feet

Order number

Description of accessories

**07.70 00 81**

### Turn bolt fastener

Order number

Description of accessories

**07.60 00 01**

cylinder lock for transparent cover

### Board guides

Order number

Description of accessories

**07.00 00 10**

Board guides

**07.00 00 11**

Board guides

### External mounting brackets

Order number

Description of accessories

**07.60 00 03**

for enclosure without connection compartment set = 2 pcs.

## Certificates

No approvals