

- + Variable possibility of combine connection compartment and profile
- + 2 enclosure sizes 28HP and 42HP
- + Optional with transparent cover
- + Variable length by profile technic

### Included in delivery

Enclosure system - depending on version either with connection compartment, swivel intermediate frame, profile and screwed lid.

## Technical data

<b>Material:</b>	Enclosure profile: DIN EN 573 EN AW-AlMgSi, Connection comparent: DIN EN 1706 EN AC- AlSi 12 (Fe)
<b>Colour:</b>	Powder coating, RAL 7043, traffic grey B
<b>Ingress protection:</b>	IP 65 to EN 60529, Outdoor application on request
<b>Temperature range:</b>	-40°C to +90°C with transparent cover: -40°C to +60°C

## Product range

Product type	Order number	Dimensions H x W x D (mm)
NT 19-21	<b>07.60 42 22</b>	285 x 161 x 239

## Accessories

### table feet

Order number

**10.07 00 19**

### 19" mounting frame

Order number

**07.60 42 81**

### Front plate

Order number

**07.60 42 30**

### mounting feet

Order number

Description of accessories

**07.70 00 81**

### Board guides

Order number

Description of accessories

**07.00 00 10**

Board guides

**07.00 00 11**

Board guides

### External mounting brackets

Order number

Description of accessories

**07.60 00 03**

for enclosure without connection compartment set = 2 pcs.

## Certificates

No approvals