



- + Aluminium profile enclosure system in 5 dimensions for data, PC and MCR technology
- + External screw channels guarantee internal area without splinter
- + Integrated guide grooves for PCB's
- + Variable length by profile system

Included in delivery

Enclosure with 2 Aluminium diecast lids and 2 multi-function profiles, not screwed

Technical data

Material:	Lid: Aluminium DIN EN 1706 EN AC-AISI 12 (Fe), Enclosure profile: DIN EN 573 EN AW-AMgSi
Colour:	Powder coating, RAL 3003, ruby red for the multi-functional profile, RAL 9005, jet black
Ingress protection:	IP 65 to EN 60529
Temperature range:	-40°C to +90°C with transparent cover: -40°C to +60°C

Product range

Product type	Order number	Dimensions H x W x D (mm)
NT 130-130 EMC	07.51 25 10	157 x 69 x 150

Accessories

battery insert unit

Order number	Description of accessories
83.90 00 03	for 9V block
83.90 00 06	for 4x AA cells

foot / connection element

Order number	Description of accessories
07.50 90 14	for stacking or mechanical connection of enclosure

Wall profile

Order number	Description of accessories
07.50 91 11	(2 pieces) to insert in system groove for wall fixing

Wall holder

Order number
07.50 90 15

PCB profile adjustable

Order number	Description of accessories
07.50 92 15	for Novotronic 130

Certificates

No approvals