

- + Variable possibility of combine connection compartment and profile
- + 2 enclosure sizes 28HP and 42HP
- + Optional with transparent cover
- + Variable length by profile technic

### Included in delivery

Enclosure system - depending on version either with connection compartment, swivel intermediate frame, profile and screwed lid.

## Technical data

<b>Material:</b>	Enclosure profile: DIN EN 573 EN AW-AlMgSi, Connection comparent: DIN EN 1706 EN AC- AlSi 12 (Fe)
<b>Colour:</b>	Powder coating, RAL 7043, traffic grey B
<b>Ingress protection:</b>	IP 65 to EN 60529, Outdoor application on request
<b>Temperature range:</b>	-40°C to +90°C with transparent cover: -40°C to +60°C

## Product range

Product type	Order number	Dimensions H x W x D (mm)
NT 19-08	<b>07.60 28 15</b>	256 x 270 x 326

## Accessories

### Socket wrench

Order number	Description of accessories
<b>07.60 00 02</b>	special version for connection room

### 19" mounting frame

Order number
<b>07.60 28 81</b>

### Front plate

Order number
<b>07.60 28 30</b>

### Spare latch

Order number	Description of accessories
<b>07.60 00 04</b>	for connection compartment lid (plastic) for NoVoTronic

### Partition wall

Order number
<b>07.60 28 85</b>

### Board guides

Order number	Description of accessories
<b>07.00 00 10</b>	Board guides
<b>07.00 00 11</b>	Board guides

### Mounting plate

Order number	Description of accessories
<b>07.28 00 30</b>	for connection compartment (28 TE version)

## Certificates

No approvals