

- + Variable possibility of combine connection compartment and profile
- + 2 enclosure sizes 28HP and 42HP
- + Optional with transparent cover
- + Variable length by profile technic

Included in delivery

Enclosure system - depending on version either with connection compartment, swivel intermediate frame, profile and screwed lid.

Technical data

| | |
|----------------------------|---|
| Material: | Enclosure profile: DIN EN 573 EN AW-AlMgSi, Connection component: DIN EN 1706 EN AC-AISI 12 (Fe) |
| Colour: | Powder coating, RAL 7043, traffic grey B |
| Ingress protection: | IP 65 to EN 60529, Outdoor application on request |
| Temperature range: | -40°C to +90°C with transparent cover: -40°C to +60°C |

Product range

| Product type | Order number | Dimensions H x W x D (mm) |
|--------------|--------------------|---------------------------|
| NT 19-06 EMC | 07.61 28 11 | 214 x 270 x 297 |

Accessories

Socket wrench

| Order number | Description of accessories |
|--------------------|-------------------------------------|
| 07.60 00 02 | special version for connection room |

19" mounting frame

| Order number |
|--------------------|
| 07.60 28 81 |

Spare latch

| Order number | Description of accessories |
|--------------------|---|
| 07.60 00 04 | for connection compartment lid (plastic) for NoVoTronic |

Partition wall

| Order number |
|--------------------|
| 07.60 28 85 |

Board guides

| Order number | Description of accessories |
|--------------------|----------------------------|
| 07.00 00 10 | Board guides |
| 07.00 00 11 | Board guides |

Mounting plate

| Order number | Description of accessories |
|--------------------|--|
| 07.28 00 30 | for connection compartment (28 TE version) |

Certificates

No approvals