



- + Aluminium profile compact commander in 2 widths
- + Applications: Compact control equipment and display systems
- + Standard integrated cooling system
- + Variable length execution by profile technology

Included in delivery

Profile enclosure body, on rear side door or screwed wall, fastening elements for front panel. Please order front panel separately

Technical data

| | |
|----------------------------|---|
| Material: | Enclosure profile: DIN EN 573 EN AW-AMgSi, Lid: Aluminium DIN EN 1706 EN AC-AISI 12 (Fe) |
| Colour: | Powder coating, lid and base: RAL 7035, light grey, Multi-functional profile: RAL 9005, jet black |
| Ingress protection: | IP 65 to EN 60529 |
| Temperature range: | -30°C to 65°C |

Product range

| Product type | Order number | Dimensions H x W x D (mm) |
|----------------|--------------------|---------------------------|
| CT 110-SL-S-GT | 20.80 11 99 | SL x 365 x 118 |

Accessories

Other accessories see Commander system accessories

Order number

Mounting set

Order number

10.03 31 01

Fixing set

Order number

Description of accessories

10.03 60 01

M5, Set = 8 pcs

Front panel

Order number

20.80 91 98

Wall holder

Order number

20.80 90 01

Handle set

Order number

20.80 90 99

locking plate

Order number

20.80 90 04

Certificates

UL 508