

Profitronic 19U



- + Aluminium electronic enclosure in 3 sizes
- + Variable length options using profile technology
- + Standard construction or version with connection compartment
- + Optional polycarbonate transparent cover

Included in delivery

Enclosure system - depending on version either with cast aluminium lids, connection compartment or transparent cover, fixing elements please order separately

Technical data

Material:	Aluminium DIN EN 573 EN AW-AMgSi, DIN EN 1706 EN AC-AISI 12 (Fe)
Colour:	Powder coating, Enclosure profile: RAL 7035, light grey, Enclosure lid: RAL 7030, stone grey
Ingress protection:	IP 65 to EN 60529, Outdoor application on request
opening angle:	Connection compartment and transparent cover: 110°
Temperature range:	Lid seal: -40°C to +80°C transparent cover: -40°C to +70°C
Other versions on request:	EMC

Product range

Product type	Order number	Dimensions H x W x D (mm)
PT 19U-06	07.28 22 11	191 x 264 x 149

Accessories

table feet

Order number

10.07 00 19

Turn bolt fastener

Order number

Description of accessories

07.00 00 17

special lock for connection compartment

07.00 00 18

Turning handle for transparent cover

07.00 00 19

cylinder lock for transparent cover

mounting feet

Order number

Description of accessories

07.70 00 81

Board guides

Order number

Description of accessories

07.00 00 10

Board guides

07.00 00 11

Board guides

External mounting brackets

Order number

Description of accessories

07.00 02 00

for enclosure without connection compartment set = 2 pcs.

Certificates

No approvals