

# Profitronic 19U



- + Aluminium electronic enclosure in 3 sizes
- + Variable length options using profile technology
- + Standard construction or version with connection compartment
- + Optional polycarbonate transparent cover

## Included in delivery

Enclosure system - depending on version either with cast aluminium lids, connection compartment or transparent cover, fixing elements please order separately

## Technical data

<b>Material:</b>	Aluminium DIN EN 573 EN AW-AMgSi, DIN EN 1706 EN AC-AISI 12 (Fe)
<b>Colour:</b>	Powder coating, Enclosure profile: RAL 7035, light grey, Enclosure lid: RAL 7030, stone grey
<b>Ingress protection:</b>	IP 65 to EN 60529, Outdoor application on request
<b>opening angle:</b>	Connection compartment and transparent cover: 110°
<b>Temperature range:</b>	Lid seal: -40°C to +80°C transparent cover: -40°C to +70°C
<b>Other versions on request:</b>	EMC

## Product range

Product type	Order number	Dimensions H x W x D (mm)
PT 19U-03	<b>07.19 31 11</b>	148 x 273 x 149

## Accessories

### Aluminium profile (Z rails)

Order number	Description of accessories
<b>07190010</b>	Aluminium profile (Z rails)

### Insulating strip

Order number	Description of accessories
<b>07.19 00 20</b>	Insulating strip

### Turn bolt fastener

Order number	Description of accessories
<b>07.00 00 17</b>	special lock for connection compartment

### Board guides

Order number	Description of accessories
<b>07.00 00 10</b>	Board guides
<b>07.00 00 11</b>	Board guides

### Mounting plate

Order number	Description of accessories
<b>07.19 00 30</b>	for connection compartment (19 TE version)

### External mounting brackets

Order number	Description of accessories
<b>07.00 01 00</b>	for enclosure with connection compartment set = 2 pcs.

## Certificates

No approvals