

Mini-Polyglas



- + Mini polyglas enclosure with hidden external hinge for MCR technology
- + Standard version or with window

Included in delivery

Enclosure consisting of base and door;
please order door lock separately, press-
in inserts in base for internal mounting

Technical data

Material:	glass fibre reinforced thermoset polyester
Certificates:	E66473
Colour:	RAL 7038, agate grey, special colour on request
Ingress protection:	IP 66 to EN 60529
Flammability:	self-extinguishing, UL 94 V-0
Insulation:	fully insulated VDE 0100
Disruptive strength:	18 KV/mm, IEC 60243-1
Toxicity:	halogen free
Surface resistance:	$>10^{12}$ Ohm to IEC 60093
opening angle:	120°
Temperature range:	-40°C to +100°C with transparent window: -40°C to +80°C

Product range

Product type	Order number	Dimensions H x W x D (mm)
MIPT 1	22.12 20 00	120 x 200 x 100

Accessories

Socket wrench

Order number	Description of accessories
10.04 70 05	phillips screw
10.04 70 03	triangular 8mm
10.04 70 04	square 8mm

locking screws

Order number	Description of accessories
21.63 00 03	triangular screw 8mm
21.63 00 04	square screw 8mm (2 pcs)
21.63 00 05	phillips screw (2 pcs)
21.63 00 24	square screw 6mm (2 pcs)

Mounting plate

Order number
10.01 12 07

External mounting brackets

Order number	Description of accessories
10.03 10 08	set = 4 pcs

Certificates

UL 508