

# Profitronic 19U



- + Aluminium electronic enclosure in 3 sizes
- + Variable length options using profile technology
- + Standard construction or version with connection compartment
- + Optional polycarbonate transparent cover

## Included in delivery

Enclosure system - depending on version either with cast aluminium lids, connection compartment or transparent cover, fixing elements please order separately

## Technical data

<b>Material:</b>	Aluminium DIN EN 573 EN AW-ALMgSi, DIN EN 1706 EN AC-AISI 12 (Fe)
<b>Colour:</b>	Powder coating, Enclosure profile: RAL 7035, light grey, Enclosure lid: RAL 7030, stone grey
<b>Ingress protection:</b>	IP 65 to EN 60529, Outdoor application on request
<b>opening angle:</b>	Connection compartment and transparent cover: 110°
<b>Temperature range:</b>	Lid seal: -40°C to +80°C transparent cover: -40°C to +70°C
<b>Other versions on request:</b>	EMC

## Product range

Product type	Order number	Dimensions H x W x D (mm)
PT 19U-04	<b>07.19 32 11</b>	148 x 253 x 149

## Accessories

### table feet

Order number

**10.07 00 19**

### Turn bolt fastener

Order number

Description of accessories

**07.00 00 17**

special lock for connection compartment

### mounting feet

Order number

Description of accessories

**07.70 00 81**

### Board guides

Order number

Description of accessories

**07.00 00 10**

Board guides

**07.00 00 11**

Board guides

### External mounting brackets

Order number

Description of accessories

**07.00 02 00**

for enclosure without connection compartment set = 2 pcs.

## Certificates

No approvals